

Ultimaker Support › 3D Printers › Ultimaker S5 › Maintenance

Replace the Ultimaker S5 Bowden tubes

January 30, 2020 09:27

The Bowden tubes guide the filament from the feeders to the print head.

Forwarding improperly cut or ground down filament through the Bowden tube could scratch or damage the inside of the tube. If this happens, the filament can no longer be forwarded to the print head smoothly. This can lead to under extrusion or other print quality issues.

After removing a Bowden tube multiple times, the tube coupling collet can wear out. If this happens, the tube coupling collet will no longer have a firm hold on the Bowden tube. In this case, the Bowden tube will move up and down during prints, which can negatively impact print quality.

If the Bowden tubes are permanently damaged, they need to be replaced. To maintain optimal print quality it is recommended to replace the Bowden tubes every year.

Disassembly

1. Start by removing the material. Go to the configuration menu, select the material you want to remove and the *Unload*. After this, turn off the printer
2. Place the print head in the front-right corner

Ask our community of experts

Go to our community



© Ultimaker Support



Reassembly

1. Take the new Bowden tube and note the two different sides. The side which is chamfered should be inserted into the feeder. This allows easier access of the filament into the Bowden tube. The flat side should be inserted into the print head
2. Insert the Bowden tube into the feeder by pressing down on the tube coupling collet in the feeder and pushing the Bowden tube all the way in. Secure the tube with the clamp clip
3. Insert the Bowden tube into the print head by pressing down on the tube coupling collet in the print head and pushing the Bowden tube all the way in. Secure the tube with the clamp clip
4. When replacing the Bowden tube from Extruder 2 (right), click the header cable clips onto the Bowden tube. Equally divide the clips over the Bowden tube



Was this article helpful?



0 out of 0 found this helpful

Comments

Articles in this section

0 comments

► Maintenance schedule of the Ultimaker S5

► Update the Ultimaker S5 firmware

► Ultimaker S5 firmware release notes

► Firmware 6.0 for the Ultimaker S-line

► Material handling and storage for the Ultimaker S5

► Cleaning the Ultimaker S5

► Lubricate the Ultimaker S5 axles

► Check for play on the Ultimaker S5 axles

► Check the tension of Ultimaker S5 short belts

- › Check for debris in the Ultimaker S5's front fan of the print head

[See more](#)

Recently viewed articles

- › Lubricate the Ultimaker S5's Z screw of the Z motor
- › How to perform a hot and cold pull
- › Clean the feeders on the Ultimaker S5
- › Check the quality of the Ultimaker S5 nozzle cover
- › Check for debris in the Ultimaker S5's front fan of the print head