

MapKit 3D

Running Xcode 16.3+ and visionOS 2.3+?

If not, download it *NOW* and Start Xcode!

Manu @stuffmc Carrasco Molina
Cocoaheads Aachen, May 22, 2025


MapKit3D_Starter.zip

- We'll do the App without Reality Composer Pro!
- A 2D Map will be shown next to our 3D Globe
- We'll stick as much possible to the MapKit Models
- We won't build an exact replica of MapKit for SwiftUI
- I might open source this as a framework after WWDC...

Preview

Preview ContentView to make sure it compiles and works.

```
struct ContentView: View {  
    var body: some View {  
        Text("Hello, 🌍").font(.extraLargeTitle)  
    }  
}
```





- See how it has a beautiful glass background in Preview!

Run

- Run in in the Simulator to make sure as well.
- Learn the basics of the Simulator
 - **Show Home with**   **H** — *Oh, a boring/empty Icon!*
 - Move around and use **Debug > Show Gaze Target**

Icon

- AppIcon in Assets.
- Use `middle` and `back` (and `front`?)



Replace the body of ContentView

```
import MapKit

var body: some View {
    Map()
}
```

Look at the bottom left corner
Apple didn't give MapKit much love in visionOS

No glass anymore in the Preview!



Fix it old school

```
#Preview(windowStyle: .automatic) {  
  ContentView()  
    .glassBackgroundEffect()  
}
```

Let's create a Sphere

Create **Map3D.swift**

A SwiftUI file

```
import RealityKit

@State private var globe: ModelEntity!
private let radius: Float = 0.4

var body: some View { realityView }

private var realityView: some View {
    RealityView { content in
        await setup()
        content.add(globe)
    }
}

private func setup() async {
    globe = ModelEntity(mesh: .generateSphere(radius: radius))
}
```

Add a Preview

```
#Preview(windowStyle: .volumetric) {  
    Map3D()  
}
```

- Because if you run the previous code, nothing will happen anyways
- Time to open that 3D Globe when the app starts!

Auto-open it on start

```
struct MapKit3D: App {
    var body: some Scene {
        WindowGroup(id: "a") { ContentView() }
        WindowGroup(id: "g") { Map3D() }.windowStyle(.volumetric) }
    }
}

struct ContentView: View {
    @Environment(\.openWindow) private var openWindow

    var body: some View { Map().onAppear { openWindow(id: "g") } }
```

- We'll use the **id a** in a minute...



Open it on the side

```
...  
    .windowStyle(.volumetric)  
    .defaultWindowPlacement { _, ctx in  
        guard let content = ctx.windows.first(where: {  
            $0.id == "a" }  
        ) else {  
            return WindowPlacement(nil)  
        }  
        return WindowPlacement(.leading(content))  
    }  
}  
}
```




Let's create a White Sphere

Map3D.swift

```
var material = UnlitMaterial()  
globe = ModelEntity(mesh: .generateSphere(radius: radius),  
                    materials: [material]  
                    )
```

- Ignore the warning, we'll mutate `material` later.



Put that image in your Asset Catalog

- `M_earth_baseColor.jpg` is approx. 18MB

Use the Texture of the 🌍!

```
guard let resource = try? await
    TextureResource(named: "M_earth_baseColor") else {
    fatalError("Unable to load texture.")
}
var material = UnlitMaterial(texture: resource)
```

Let's Add Markers/Annotation

- I can see New Delhi & Sidney
- We'll do this with RealityKit Attachments
- They are SwiftUI placed on an Entity

Create **Extension.swift**

```
extension CLLocationCoordinate2D {  
    static let zero      = CLLocationCoordinate2DMake(0, 0)  
    static let lima      = CLL...(-12.046373, -77.042755)  
    static let sidney     = CLL...(-19.259970, 146.792007)  
    static let newDelhi   = CLL...(28.613939, 77.209023)  
    static let gaza       = CLL...(31.354675, 34.308826)  
    static let quito      = CLL...(-0.180653, -78.467834)  
    static let all = [sidney, newDelhi, lima, zero, quito, gaza]  
}
```

- 🇵🇪 🇸🇦 ❤️ and you'll see why it's useful to have Lima & Gaza

First display on the 2D Map

```
Map {  
  Marker("🇵🇸 Gaza", coordinate: .gaza)  
  Marker("🇮🇳 New Delhi", coordinate: .newDelhi)  
}
```

Add a second one to “dezoom” the map

Models.swift mimics Markers

```
import MapKit
import SwiftUI

struct Marker3D {
    var text: String
    var coordinate: CLLocationCoordinate2D

    init(_ text: String, coordinate: CLLocationCoordinate2D) {
        self.text = text
        self.coordinate = coordinate
    }
    var marker: Marker<Text> { .init(text, coordinate: coordinate) }
} // We'll use this in 2D...
```

Add an **AppModel** in that file

```
@Observable class AppModel {  
    static let radius: Float = 0.4  
    var markers = [  
        Marker3D("🇪🇨 Quito",      coordinate: .quito),  
        Marker3D("🇵🇸 Gaza",      coordinate: .gaza),  
        Marker3D("🇵🇪 Lima",      coordinate: .lima),  
        Marker3D("🇦🇺 Sidney",    coordinate: .sidney),  
        Marker3D("🇮🇳 New Delhi", coordinate: .newDelhi),  
        Marker3D("🌐 Zero",      coordinate: .zero)  
    ]  
}
```


Pass the Model

```
struct MapKit3D: App {  
    let model = AppModel()  
  
    var body: some Scene {  
        WindowGroup(id: "a") {  
            ContentView()  
                .environment(model)  
        }  
        WindowGroup(id: "g") {  
            Map3D()  
                .environment(model)  
        }  
        ...  
    }  
}
```

```
#Preview(windowStyle: .automatic) {  
    ContentView()  
        .glassBackgroundEffect()  
        .environment(AppModel())  
}
```

Use the App Model

```
struct ContentView: View {
    @Environment(\.openWindow) private var openWindow
    @Environment(AppModel.self) private var model

    var body: some View {
        Map {
            ForEach(model.markers) { $0.marker.tint(.yellow) }
        }
        // -----
        // I can't see those Red Pins!
    }
}
```

Requires that 'Marker3D' conform to 'Identifiable'

```
extension Marker3D: Identifiable {  
    var id: String { "\((Int(coordinate.latitude  
        )), \((Int(coordinate.longitude))"  
    }  
}
```


Move the Content of the Map

```
Map { Content2D() }

struct Content2D: MapContent {
    @Environment(AppModel.self) private var model

    var body: some MapContent {
        ForEach(model.markers) {
            $0.marker
                .tint(.yellow)
        }
    }
}

// I've tried/failed a Content3D...
```

Create the Attachments

```
@Environment(AppModel.self) private var model

RealityView { content, attachments in
    ...
} attachments: {
    ForEach(model.markers) { marker in
        Attachment(id: marker.coordinate) {
            Text(marker.text).padding().glassBackgroundEffect()
        }
    }
}
```

'CLLocationCoordinate2D' does not conform to expected type 'Hashable'

```
extension CLLocationCoordinate2D: @retroactive Hashable {  
    public static func == (lhs: Self, rhs: Self) -> Bool {  
        lhs.latitude == rhs.latitude && lhs.longitude == rhs.longitude  
    }  
  
    public func hash(into hasher: inout Hasher) {  
        hasher.combine(latitude)  
        hasher.combine(longitude)  
    }  
}
```



Add the Attachments

```
RealityView { content, attachments in
    add(attachments)
} attachments: { ... }

private func add(_ attachments: RealityViewAttachments) {
    for marker in model.markers {
        if let attachment = attachments.entity(for: marker.coordinate) {
            globe.addChild(attachment)
        }
    }
}
```

Wait, where is it?

- Can anyone guess where it is?
- Hint: We didn't position the entity anywhere
- So...
- Zoom inside your globe...



Yes, it's inside!


- All of them, stacked on top of each other
- At position 0, 0, 0 in the 3D Space!

Position the Attachments

```
if let attachment = attachments.entity(for: marker) {  
    attachment.position = /* what? */  
    entity.addChild(attachment)  
}
```

- We need to map Lat/Lon to the 3D Space!
- [StackOverflow](#) to the rescue! (**Screw you, ChatGPT!**)

```
// In the Cartesian coordinate system, the conversion is:  
x = RADIUS * cos(lat) * cos(lon) // longitude (meeting the equator)  
y = RADIUS * cos(lat) * sin(lon) // latitude (meeting Greenwich)  
z = RADIUS * sin(lat)           // goes through the poles.
```



1

If your trigonometric functions expect radians (which they do),
you will need to convert your longitude and latitude to radians first.

¹CC: [flickr/photos/rutty/492385781](https://www.flickr.com/photos/rutty/492385781/), re-thinkingthefuture.com

Add to your **Marker3D**

```
func coords(for radius: Float) -> SIMD3<Float> {  
    [0, 0, 0]  
}
```

- We'll return X, Y, Z
- We'll write the code in a minute...

Time for a Unit Test

- New Target, Test
- New File, Swift Testing Unit Test
- `Test.swift`, No Briding Header!
- Only add in the Test Target
- Add `Models.swift` in that Target

```
import Testing

struct Tests {
  private let coord = Marker3D("Quito", coordinate: .quito)
                                .coords(for: 0.4)

  @Test func coords() async throws {
    #expect(coord.x == 0.07996686)
    #expect(coord.y == -0.39192313)
    #expect(coord.z == -0.0012611939)
  }
}
```

- Start the Unit Test, should be red

Fix coords and the Unit Test

```
let lat = Float(coordinate.latitude) * .pi / 180
let lon = Float(coordinate.longitude) * .pi / 180
let coords: SIMD3<Float> = [
    radius * cos(lat) * cos(lon),
    radius * cos(lat) * sin(lon),
    radius * sin(lat)
]
return coords
```



Houston, we have **TWO** Problems

1. Gaza in the Pacific, New Delhi in Russia, ...
2. Attachments face to us
 - They should face the Globe!
 - Replace `.position =` with `.look(at: from:)`
 - Can you guess the `at`?
 - `[0,0,0]`, the center of the earth!



```
attachment.look(  
  at: [0,0,0],  
  from: coords,  
  relativeTo: globe  
)
```


relativeTo optional, but ...




In RealityKit:



Coordinate spaces



SwiftUI



Rotate 90° on your X axis!

```
from: coords * simd_quatf(angle: .pi/2, axis: [1, 0, 0])
```

The compiler is unable to type-check this expression in reasonable time; try breaking up the expression into distinct sub-expressions

OR

Cannot convert value of type '*simd_quatf*' to expected argument type '*simd_float3x3*'

Let's break up & fix in **Extension.swift**

```
from: coords * (pi / 2).rotateX // We'll need it later

extension Float {
    var rotateX: simd_float3x3 {
        simd_matrix3x3(simd_quatf(angle: self, axis: [1, 0, 0]))
    }
}

@Test func coordsRotated() ... // Create this now
```


Lima is up again!

- I can tell the latitudes are good!
- What's wrong with our Longitude?
- Our texture doesn't start at Greenwich
 - But left from Alaska, at -90° !



We need to slide the texture!

```
var material = UnlitMaterial(texture: resource)

material.textureCoordinateTransform =
    .init(offset: SIMD2<Float>(x:0.5, y: 0))
```

- Now we see America instead of Asia
- And our Markers are correct! 🎉
- I told you I'll make this `var` useful!

Easier, take this texture

```
let material = UnlitMaterial(texture: resource)
```

- Replace with `M_earth_baseColor_greenwich.jpg`
- Otherwise it will make the code more complicated
- Remove the `.textureCoordinate` and make `let material` 🎉

Let's travel a bit more



```
static let la      = (34.052235 , -118.243683)
static let phoenix = (33.44825 , -112.07662 )
static let dallas  = (32.77557 , -96.79560 )
static let madrid  = (40.416775 , -3.703790)
```

HOLLYWOOD

Adding new attachments

```
NavigationStack {
  Map { ... }
  .toolbar {
    Button("Add") {
      model.markers.append(Marker3D("🇺🇸 LA", coordinate: .la) )
      model.markers.append(Marker3D("🇪🇸 Madrid", coordinate: .madrid))
    }
  }
  .font(.extraLargeTitle)
}
.onAppear {
  openWindow(id: "g")
} // This is to simulate a more sophisticated UI for adding/searching...
```

Added to 2D and 3D, but...

- Why nothing happens?
- We are `@Observable`, `@State`, `@Environment`
 - Everything good, no?
- RealityKit won't refresh all the `RealityView`
 - Only `attachments`: and ...

Add the update: block

```
RealityView { content, attachments in
    ...
} update: { content, attachments in
    if let globe {
        add(attachments)
    }
} attachments: {
    ...
}
```




A bug? PBKAC...

```
content.remove(globe)  
add(attachments)  
content.add(globe)
```

- Only in the `update` block
- I'm not happy about it...

Now let's add a Marker when we tap the globe!

```
realityView
    .gesture(spatialGesture)

private var spatialGesture: some Gesture {
    SpatialTapGesture().targetedToAnyEntity().onEnded {
        var pos = $0.convert($0.location3D, from: .local, to: .scene)
        pos = globe.convert(position: pos, from: nil)
        // We need revert our orientation
        pos = pos * (-.pi / 2).rotateX
        print(pos)
    }
}
```


Nothing prints **because no Components!**

```
globe.components.set(  
    [  
        CollisionComponent(shapes:  
            [.generateSphere(radius: AppModel.radius)]  
        ),  
        InputTargetComponent()  
    ]  
)
```

```
private let converted = SIMD3<Float>(
    -0.027481655,
    -0.31684208,
    -0.23480688
)
var pos: SIMD3<Float> { converted * (-.pi/2).rotateX }

@Test func convert() async throws {
    #expect(pos.x == -0.027481655)
    #expect(pos.y == 0.23480685)
    #expect(pos.z == -0.3168421)
}
```

Get lat/lon from X,Y,Z

```
extension SIMD3<Float> {  
    func latitude(for radius: Float) -> Double {  
        Double(asin(z / radius) * 180 / .pi)  
    }  
    var longitude: Double { Double(atan2(y, x) * 180 / .pi) }  
}  
  
@Test func latlon() async throws // write this ...
```


Reverse Geolocation!

```
Task { await reverse(latitude: pos.latitude(for: AppModel.radius),
                    longitude: pos.longitude)
}
private let coder = CLGeocoder()
private func reverse(latitude: Double, longitude: Double) async {
    let location = CLLocation(latitude: latitude, longitude: longitude)
    if let placemark = try! await coder.reverseGeocodeLocation(location).first {
        model.markers.append(
            Marker3D(placemark.locality ?? "?", coordinate: location.coordinate)
        ) } }

@Test func placemark() // write this...
```

Let's go from Dallas to LA!

```
struct MapPolyline3D {
    private(set) var coordinates: [CLLocationCoordinate2D]

    var polyline: MapPolyline {
        .init(coordinates: coordinates)
    }
}

class AppModel {
    var polylines = [MapPolyline3D]()

    init() {
        polyline = [MapPolyline3D(coordinates: [.la, .dallas])]
    }
}
```

```
Map(initialPosition: .region(.init(center: .phoenix,  
    span: .init(latitudeDelta: 15, longitudeDelta: 15)))) {  
    Content2D()  
}  
var body: some MapContent {  
    ...  
    ForEach(model.polylines) {  
        $0.polyline.stroke(.blue, lineWidth: 5)  
    }  
}
```



Calculate the points between the route

```
struct MapPolyline3D {  
    mutating func calculate() async {  
        guard let source = coordinates.first,  
              let destination = coordinates.last else { return }  
        let request = MKDirections.Request()  
        ...  
    }  
}
```



```

request.source = MKMapItem(placemark: MKPlacemark(coordinate: source,
                                                    addressDictionary: nil))
request.destination = MKMapItem(placemark: MKPlacemark(coordinate: destination,
                                                         addressDictionary: nil))
request.transportType = .automobile
do {
    if let route = try await MKDirections(request: request)
        .calculate().routes.first {
        let count = route.polyline.coordinates.count
        if count > 2 {
            coordinates = []
            let indices = stride(from: 0,
                                through: count - 1,
                                by: (count - 1) / 251) // Approx UInt8
            indices.forEach { coordinates.append(route.polyline.coordinates[$0]) }
        }
    } } catch {
        print(error)
    }
}

```


Value of type 'MKPolyline' has no member 'coordinates'

```
public extension MKMultiPoint {  
    var coordinates: [CLLocationCoordinate2D] {  
        var coords = [CLLocationCoordinate2D](repeating: CLLocationCoordinate2DInvalid,  
                                                count: pointCount)  
  
        getCoordinates(&coords, range: NSRange(location: 0, length: pointCount))  
        return coords  
    }  
}
```

Augment to calculate...

```
class AppModel {  
    var polylines = [MapPolyline3D]()  
  
    init() {  
        var polyline = MapPolyline3D(coordinates: [.la, .dallas])  
        Task {  
            await polyline.calculate()  
            self.polylines = [polyline]  
        }  
    }  
}
```

Add



One way of plotting this route in 3D ...

```
} attachments: {  
  ...  
  ForEach(model.polylines.coordinates) {  
    Attachment(id: $0) {  
      Circle().frame(width: 10,  
                     height: 10)  
      .foregroundStyle(Color.yellow)  
    }  
  }  
}
```

```
extension [MapPolyline3D] {  
  var coordinates: [CLLocationCoordinate2D] {  
    flatMap(\.coordinates)  
  }  
}  
  
extension CLLocationCoordinate2D:  
  @retroactive Identifiable {  
  
  public var id: String {  
    "\((Int(latitude)), \((Int(longitude)))"  
  }  
}
```

```
private func add(_ attachments: RealityViewAttachments,
                 for coordinate: CLLocationCoordinate2D) {
    if let attachment = attachments.entity(for: coordinate) {
        attachment.add(coordinate, to: globe)
    }
}

private func add(_ attachments: RealityViewAttachments) {
    model.markers.forEach {
        add(attachments, for: $0.coordinate)
    }
    model.polylines.coordinates.forEach {
        add(attachments, for: $0)
    }
}
```


- But it's just points, right?!
- Yes, and that's okay (for now)
- Because even if you zoom... 250 points!



Polygons, boundingBoxes, States

- Sweet home Alabama

```
extension [CLLocationCoordinate2D] {  
  static let alabama = [  
    CLLocationCoordinate2DMake(30.1375217437744,  
                               -84.8882446289062), // South West (Bristol, FL)  
    CLLocationCoordinate2DMake(35.0080299377441,  
                               -88.4731369018555), // North East (Michie, TN)  
  ]  
}
```

```
var box: [CLLocationCoordinate2D] {
    if count != 2 {
        assertionFailure("Only allowed with 2 coordinates, not \(count)")
        return []
    }
    guard let first, let last else {
        assertionFailure("Could not get min/max (first/last)")
        return []
    }
    return [
        CLLocationCoordinate2DMake(first.latitude, first.longitude),
        CLLocationCoordinate2DMake(first.latitude, last.longitude),
        CLLocationCoordinate2DMake(last.latitude, last.longitude),
        CLLocationCoordinate2DMake(last.latitude, first.longitude)
    ]
}
```

Poly ❤️ first in 2D

```
class AppModel {  
    ...  
    var polygons = [MapPolygon3D(coordinates: .alabama.box)]  
}  
var body: some MapContent {  
    ...  
    ForEach(model.polygons) {  
        $0.mapPolygon  
            .tint(.gray) // .opacity?  
    }  
    ...  
}
```





Quito



Lima


Add



Now let's create a Polygon in 3D

```
extension ModelEntity {  
    static func with(coordinates: [CLLocationCoordinate2D]) async  
        -> ModelEntity {  
  
        let points = coordinates.map {  
            $0.simd3(for: AppModel.radius * 1.02)  
        }  
        ...  
    }  
}
```

```
...  
var descriptor = MeshDescriptor()  
descriptor.positions = MeshBuffers.Positions(points)  
descriptor.primitives = .polygons(  
    [UInt8(points.count)],  
    points.indices.map { UInt32($0) }  
)  
let resource = try! await MeshResource(from: [descriptor])  
return ModelEntity(mesh: resource)
```


The background of the slide is a satellite image of Earth, showing the Americas. A thick, wavy yellow line is drawn across the continent of North America, extending from the Gulf of Mexico up to the Canadian border.

```
RealityView { content, attachments in
  ...
  await globe.addChild(
    ModelEntity.with(coordinates: .alabama.box)
  )
}
```


- But now... crickets...
- Except if you zoom, pan, ...


New 🇮🇳 .

• 🇸🇦 Gaza



Zero 🌍





78



Reverse the dots!

```
points.indices.reversed().map { UInt32($0) }
```

- Thanks Matthias Weber!
- ... aaand, that's it!

Pizzatime!

m@carrascomolina.com

0160 36 55 761

Thanks!